



Scan the QR code
for more details

Project Page

AtlasGS: Atlanta-world Guided Surface Reconstruction with Implicit Structured Gaussians


Xiyu Zhang* · Chong Bao* · Yipeng Chen · Hongjia Zhai · Yitong Dong

Hujun Bao · Zhaopeng Cui · Guofeng Zhang†

State Key Lab of CAD & CG, Zhejiang University



The Goal of AtlasGS



Dense posed Images of the **Structural** Scene,
like indoor scenes and city scenes.

Fast and **Accurate** Surface Reconstruction

Introduction

TL;DR: We propose a new Gaussian Splatting representation under Atlanta world assumption for indoor and urban surface reconstruction.

Previous Methods

Gaussian Based Methods (2DGS):

Fast training and rendering (< 1h)

Discrete representation leads to discontinuous Surfaces

NeRF Based Methods (MonoSDF):

Smooth but low refrenquency

Hours for training (> 7h)

Both suffer from multiview inconsistency of monocular geometry priors

Ours:

Implicit-Structured GS: Combines MLP smoothness with Gaussian details.

Structural Priors: Atlanta-world guided regularization fixes Multiview inconsistency.

SOTA Performance: Fast training (< 30 mins) with accurate geometry.

Methods

(a) Implicit Structured Gaussian Splatting

We construct a sparse feature grid $\mathcal{V}$ and decode attributes for K local Gaussians at voxel v via geometry and semantic MLPs $\mathcal{M}_g, \mathcal{M}_s$

$$\{\alpha_k, s_k, q_k, c_k\} = \mathcal{M}_g(\mathcal{V}_g(v), d), \quad z_k = \mathcal{M}_s(\mathcal{V}_s(v))$$

$$p_k = v + l \cdot \Delta_k$$

Differentiable rasterization renders attributes (color C , depth D , semantics Z):

$$C = \sum_{i \in \mathcal{N}} c_i \alpha_i \prod_{j=1}^{i-1} (1 - \alpha_j)$$




Figure 1: Overview of AtalsGS.

(b) Atlanta-world Guided Planar Regularization We model the scene with Atlanta-world assumption (gravity n_g and offsets d):

$$\pi_{floor} : d_f + n_g \cdot p = 0, \quad \pi_{ceiling} : d_c - n_g \cdot p = 0$$

We enforce global structure via **3D Global** $\mathcal{L}_{3D}$ and **2D Local** $\mathcal{L}_{2D}$ regularization:

$$\mathcal{L}_{3D} = \underbrace{\sum p_{\parallel} (1 - |n_g^{\top} n_i|) + \sum p_{\perp} |n_g^{\top} n_i|}_{\text{Normal Alignment}} + \underbrace{\sum p_c |d_c - n_g^{\top} p_i| + \sum p_f |d_f + n_g^{\top} p_i|}_{\text{Planar Constraint}}$$

$$\mathcal{L}_{2D} = \sum p_w |N_d \cdot n_g| + \sum p_{c,f} (1 - |N_d \cdot n_g|)$$

where $p_{\parallel}, p_{\perp}, p_c, p_f, p_w$ are probabilities for parallel, perpendicular, ceiling, floor, and wall regions.

(c) Optimization The framework is jointly optimized with photometric loss, semantic supervision, and monocular geometry priors (depth $\hat{D}$ and normal $\hat{N}$):

$$\mathcal{L} = \mathcal{L}_{rgb} + \lambda_{sem} \mathcal{L}_{sem} + \lambda_{reg} \mathcal{L}_{reg} + \lambda_{prior} (\mathcal{L}_{depth} + \mathcal{L}_{normal})$$

Experiments

Quantitative Results of Surface Reconstruction

Table 1: Quantitative comparison of on indoor scenes.

Category	Methods	Replica [52]					ScanNet++ [51]				
		Acc↓	Comp↓	Prec↑	Recall↑	F-score↑	Acc↓	Comp↓	Prec↑	Recall↑	F-score↑
Implicit	ManhattanSDF [13]	4.76	5.59	68.80	66.40	67.57	3.96	4.98	77.30	76.16	76.67
	MonoSDF [14]	4.14	5.38	75.50	70.89	73.08	4.05	5.57	76.25	75.16	75.65
	Scaffold-GS [54]	8.58	11.27	63.53	54.91	58.89	23.11	15.36	28.18	31.75	29.78
Explicit	2DGS [10]	4.76	6.34	74.54	65.37	69.64	16.53	17.91	22.84	20.79	21.71
	DN-Splatter [44]	16.97	15.52	32.67	30.90	31.75	16.77	15.05	22.42	21.97	22.16
	GSRec [17]	4.90	6.89	73.32	67.69	70.37	9.37	9.13	47.12	53.81	50.14
	Ours	2.25	4.08	93.18	82.22	87.35	3.22	4.09	87.59	87.47	87.48

Table 2: Quantitative comparison of on ScanNet.

Category	Methods	Acc↓	Comp↓	Prec↑	Recall↑	F-score↑	Time ↓	FPS ↑
Implicit	ManhattanSDF [13]	4.25	5.23	72.39	63.18	67.25	> 7 h	< 10
	MonoSDF [14]	4.25	4.76	73.53	69.18	71.21	> 7 h	< 10
	Scaffold-GS [54]	9.47	7.99	51.41	49.08	50.17	12 mins	279
Explicit	2DGS [10]	11.46	13.89	43.15	36.17	39.27	11 mins	118
	DN-Splatter [44]	13.54	14.77	21.71	18.94	20.22	12 mins	145
	GSRec [17]	6.71	5.40	60.36	66.63	63.30	35 mins	261
	Ours	3.62	3.93	80.31	75.85	77.98	27 mins	70

Table 3: Quantitative comparison of on Matrix City.

Methods	Acc↓	Comp↓	CD↓
GaussianPro [59]	0.102	0.081	0.091
Scaffold-GS [54]	0.328	0.303	0.316
GSRec [17]	0.048	0.175	0.112
2DGS [10]	0.115	0.098	0.106
Ours	0.022	0.034	0.028

Qualitative Results of Surface Reconstruction




Figure 2: Qualitative comparison of indoor scene reconstruction.




Figure 3: Qualitative comparison of outdoor scene reconstruction.