

Beyond Chamfer Distance

Granular, order-aware evaluation metrics for online mapping

Chouaib Bencheikh Lehocine Adam Lilja Junsheng Fu Lars Hammarstrand

Zenseact AB · Chalmers University of Technology


NeurIPS 2026 – Evaluations & Datasets

SOSPA – order-aware single-instance metric | **PLD** – soft multi-instance metric

The problem: Chamfer Distance + AP

Online map estimation (OME) predicts map elements as **ordered polylines/polygons**.

Evaluation uses **Chamfer Distance (CD)** + **Average Precision (AP)**



Predictions are diagonally offsetted and one instance includes misordered points


↑ mAP $\in [0, 1] = 1.0$ (indicating perfect detection)

↓ mPLD $\in [0, 1] = 0.82$ indicating degraded detection.

The problem: Chamfer Distance + AP

- CD **ignores point ordering** (polyline geometry)
- CD is coarse, outlier-sensitive, **not a metric**
- AP's hard TP/FP thresholds **discard positional accuracy**

Goal: an **order-aware**, **granular**, **metric** framework that jointly scores **detection and geometrical accuracy**



Predictions are diagonally offset and one instance includes misordered points


↑ mAP $\in [0, 1] = 1.0$ (indicating perfect detection)

↓ mPLD $\in [0, 1] = 0.82$ indicating degraded detection.


Pillar 1 — SOSPA: order-aware single-instance metric

SOSPA = *Sequence Optimal Sub-Pattern Assignment*

- adapts GOSPA from unordered sets to **ordered sequences** of points.
- SOSPA is a **true metric**



Partial match: 3 pairs matched, spurious points skipped at cost $c/2$ each.



Matched: $(x_1, y_1), (x_2, y_3), (x_4, y_4)$; skipped x_3, y_2
SOSPA = 1.0 vs. CD = 0

Order error: same points, swapped order — SOSPA penalizes it; CD/GOSPA score 0.

Pillar 2 — PLD: soft multi-instance metric

PLD = *Polyline Localization and Detection*: instantiates **Probabilistic GOSPA** with normalized SOSPA as base metric.

$$d_{\text{PLD}}^{(c,p)}(\mathbf{X}, \mathbf{Y}) = \left[\min_{\theta} \sum_{(i,j) \in \theta} \left(\min(r_i, r_j) \bar{d}_{\text{SOSPA}}(x_i, y_j)^p + \frac{1}{2} |r_i - r_j| \right) + \frac{1}{2} \sum_{\text{unmatched}} r \right]^{1/p}$$
$$\bar{d}_{\text{PLD}} = \frac{2 d_{\text{PLD}}}{\left(\frac{1}{2} (R_{\mathbf{X}} + R_{\mathbf{Y}}) \right)^{1/p} + d_{\text{PLD}}} \in [0, 1], \quad R_{\mathbf{X}} = \sum_i r_i$$

- Replaces hard TP/FP thresholding with a **confidence-weighted soft assignment**
- Confidences $r_i \in [0, 1]$;
- **metric** for $p = 1$;
- mean over classes $\Rightarrow$ **mPLD** (analogue of mAP)


Interpretable decomposition
($p = 1$)

$$\bar{d}_{\text{PLD}} = \underbrace{\bar{e}_{\text{loc.}}}_{\text{TP geometry}} + \underbrace{\bar{e}_{\text{det.}}}_{\substack{\text{misses+false alarms} \\ \text{+conf. mismatch}}} \in [0, 1]$$

Benchmarks: PLD ranks methods *and* diagnoses them

Method	nuScenes		AV2	
	↑CD-AP	↓PLD	↑CD-AP	↓PLD
MapTRv2	0.183	0.936	0.492	0.879
StreamMapNet	0.219	0.928	0.512	0.856
MapTracker	0.357	0.884	0.642	0.781

$c = 1.5, p = 1.$



- mPLD **preserves the CD-mAP ranking**: MapTracker > StreamMapNet > MapTRv2.
- Detection error dominates localization by 2–4×

Takeaways

- **SOSPA** — order-aware, granular, outliers-robust single-instance similarity
- **PLD** — soft multi-instance metric that scores **localization** and **detection**
- PLD preserves AP rankings
- PLD exposes that **detection is the current bottleneck** in online mapping

Code: github.com/zenseact/SOSPA


Paper: [arXiv:2605.22578](https://arxiv.org/abs/2605.22578)



[arXiv:2605.22578](https://arxiv.org/abs/2605.22578)


Additional Materials

Qualitative example: perfect AP, imperfect map



MapTracker on nuScenes R_{100} : $\uparrow AP$ is 1.0 for crossings and boundaries, 0.0 for dividers; $\downarrow PLD$ gives graded, per-class scores and **separates localization from detection error**.

Why it matters: toy cases CD/FD-AP cannot separate



Case	PLD	Loc.	Det.	CD-AP	FD-AP
(a) FP gran. (i)	0.000	0.000	0.000	1.0	1.0
(a) FP gran. (ii)	0.800	0.000	0.800	1.0	0.0
(b) TP gran. (i)	1.000	0.000	1.000	0.0	0.0
(b) TP gran. (ii)	0.778	0.222	0.556	0.0	0.0
(c) Disordered (i)	0.593	0.593	0.000	1.0	1.0
(c) Disordered (ii)	0.778	0.222	0.556	1.0	0.0

$c = 0.5$, $p = 1$; CD-/FD-AP use threshold 0.5.

- CD-AP (and often FD-AP) return **identical, uninformative** scores across all three cases.
- **PLD distinguishes** every case and attributes each error to **localization** vs. **detection**.

Long range and cost: FD–AP vanishes, PLD stays informative


Method	↑ CD–mAP		↑ FD–mAP		↓ mPLD	
	R_{60}	R_{100}	R_{60}	R_{100}	R_{60}	R_{100}
MapTRv2	0.278	0.183	0.150	0.029	0.893	0.936
StreamMapNet	0.335	0.219	0.180	0.031	0.866	0.928
MapTracker	0.390	0.357	0.222	0.091	0.822	0.884

nuScenes; $c = 1.5$, $p = 1$; FD thresholds $\{1, 2, 3\}$ m at both ranges.


Evaluation time (StreamMapNet, nuScenes R_{60} , 64 workers)	CD–mAP	mPLD
Runtime (s)	38.0	37.8

- FD–mAP at R_{100} is ≈ 0.03 – 0.09 : **uninformative** for comparing methods.
- mPLD keeps a clear spread and the same ranking at R_{100} (0.936 / 0.928 / 0.884).
- mPLD costs the same as CD–mAP (≈ 38 s).


Near-perfect AP still hides errors (AP > 0.95)



PLD (mean 0.54)



Localization



Detection

StreamMapNet predictions with $AP > 0.95$ (nuScenes R_{60}): PLD is far from zero, and the residual error is mostly **detection** (confidence mismatch, misses, false alarms).

Pillar 1 — SOSPA: Equation

SOSPA = *Sequence Optimal Sub-Pattern Assignment*

- adapts GOSPA from unordered sets to **ordered sequences** of points.
- SOSPA is a **true metric**

$$d_{\text{SOSPA}}^{(c,p)}(\mathbf{x}, \mathbf{y}) = \left(\min_{\theta \in \Theta^{\text{ord}}} \sum_{(i,j) \in \theta} d(x_i, y_j)^p + \frac{c^p}{2} (n_x + n_y - 2|\theta|) \right)^{1/p}$$
$$\bar{d}_{\text{SOSPA}} = \frac{2 d_{\text{SOSPA}}}{\left(\frac{c^p}{2} (n_x + n_y) \right)^{1/p} + d_{\text{SOSPA}}} \in [0, 1]$$

- SOSPA is a **true metric**